



Premium Range **BRIGHT**

Experience the European difference

BP595 Truck/OTR Tyre Changer



WINNERS
IMPORTS



Model: BP595


Product: Truck/OTR tyre changer

Description: Designed for versatility and efficiency, this truck/OTR tyre changer accommodates rim diameters from 14" to 60". With robust construction and advanced hydraulic controls, it ensures smooth operation and precise handling of oversized tyres. Ideal for busy workshops, its user-friendly design enhances productivity while maintaining safety, making tyre changes quicker and more efficient than ever. Perfect for both commercial and heavy-duty applications.

Features:	Benefits:
Designed and Engineered in Europe	Italian software
Wide Rim Diameter Range (14" - 60")	Capable of handling large tyres, including those from trucks, buses, agricultural, and industrial vehicles.
Pneumatic Bead Breaker	Provides strong and efficient bead breaking for large, tough tyres, ensuring quick and damage-free removal
Self-Centering Turntable	Ensures accurate positioning of large tyres for secure mounting and demounting.
Heavy-Duty Construction	Built for durability, capable of handling the demands of high-volume and large-tyre applications in professional settings.
Powerful Clamping System	Strong, non-slip jaw clamps hold large tyres securely in place throughout the tyre-changing process.
Hydraulic System	Provides smooth, powerful operation, especially useful for handling oversized and heavy tyres
User-Friendly Controls	Designed with intuitive controls to simplify operation, making it accessible for operators of various skill levels.
Versatile Application	Suitable for various types of tyres, from standard to large commercial and industrial tyres.
	Versatility for Large Tyres: With its wide rim range, the BP595 is ideal for workshops that handle a variety of oversized tyres, from heavy-duty trucks to industrial equipment.
	Increased efficiency: The powerful pneumatic bead breaker and hydraulic system ensure quick and easy mounting and demounting of large tyres, reducing overall work time
	Reduced Risk of Damage: The self-centering turntable and non-slip clamps minimize the risk of damaging rims or tyres, ensuring a safer tyre-changing process.

	Durability and reliability: The heavy-duty construction and robust components ensure long-lasting performance, even in high-demand environments.
	Improved safety: The machine's design and powerful clamping system hold large tyres securely, reducing the risk of operator injury and improving overall safety
	Ease of use: The user-friendly controls make it simple for operators to manage the tyre-changing process, improving workflow efficiency and reducing operator fatigue.
Training available	Technicians can be professionally trained to use the machine and get the maximum benefit from it.
1 year warranty	The machine will be repaired if there are any factory faults and can be replaced if required.
Spares available	Should you have a breakdown you will not have to wait for your machine to be repaired. If there is anything we don't have, we fly it in directly from the Suppliers.

Technical information	
Rim diameter	14" - 60"
Max wheel diameter	2900 mm
Wheel width	1600 mm
Hydraulic power	130 - 150 bar
Hydraulic station motor power	380v / 350Hz /3P 1.5Kw
Main shaft motor power	380v / 350Hz /3P 4Kw
Max wheel weight	2500 kg
Rotation per minute	5 rpm



Colors and designs may differ

10 Keymax Park, 1006 Ergon road, Lyttelton Manor, Gauteng